



Inferno Auto System

Sound Barrier

Inferno Auto System is a vehicle alarm system. It can function as a Sound Barrier or as a traditional siren. Inferno Auto System effectively stops intruders in their tracks by generating a patented unbearable pattern, frequency and intensity noise. Inferno Auto System covers effectively the total volume of the cargo department.



- **Keeps the cargo safe**
- **Generates an unbearable sound**
- **Sabotage protected with battery backup**
- **Easy to install**

Installation of the Inferno Auto System cheats the intruder of the few minutes that could be used between alarm activation and arrival of security or police, protecting the secured areas for that crucial period of time and continuing for the duration of continuous signal.

As a Sound Barrier, Inferno Auto System causes a person to immediately modify their behavior, typically observed as autonomic protective impetus to place ones hands on their ears followed by body motion to immediately remove oneself from the intensity zone.

It is as a behavior modifying Sound Barrier that the value of the patented frequency pattern is achieved. It can be applied to quell, repel or control aggressive, malicious and riot behaviors. This aspect has been applied for protecting Russian nuclear weapons, stores, offices, and distribution plants.

As a siren, Inferno Auto System is unmistakably loud with a unique intolerable attention getting frequency pattern that clearly stands out from background noise.

Inferno Auto System includes Inferno Intenso and an infrared motion detector. It is connected to the vehicles central locking system.

Inferno Auto System has built-in sabotage protection and a battery. The outer casing is made of aluminium and steel which makes it sturdy and durable.

Protective volume	Directional or to protect a volume up to 150 cubic meters/5250 cubic feet
Dimensions	L = 685 mm/26.97 in W = 106 mm/4.17 in D = 40 mm/1.58 in
Weight	1.7 kg/ 3.7 lb
Frequency range	2 - 5 kHz
Acoustic effect	125 -127 ±1 dB(A) @ 1 m/3.28 ft, user selectable
Battery backup	9.6 V, 1800 mAh, Ni-MH
Battery lifetime	3 years
Power consumption	12 - 16 V DC, < 150 mA
Function time at cont. signal	> 30 minutes
Standby without charge	Up to 72 hours
Temperature range	-10 — +60 (C), 14 — 140 (F)

Indusec AB

Kampementsgatan 30
SE-115 38 Stockholm, Sweden
Tel: +46 8 4461830, Fax: +46 8 4461831
E-mail: info@inferno.se

www.inferno.se

Dr. Maurice Goldman
Managing Director US
Tel: 631 235 9500
E-mail: maurice@inferno.se